



Adaptors and Reducers

Type 476

ATEX

Flameproof and Increased Safety

Adaptor
 Reducer

ADAPTOR AND REDUCER SELECTION TABLE

		Male Thread															
		Metric								NPT							
		M16	M20	M25	M32	M40	M50	M63	M75	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
Female Thread	Metric	M16															
		M20															
		M25															
		M32															
		M40															
		M50															
		M63															
		M75															
	NPT	1/2"															
		3/4"															
		1"															
		1 1/4"															
		1 1/2"															
		2"															
		2 1/2"															
		3"															

General Information

All Metric entry threads are 1.5mm pitch medium fit.

Materials & Finishes

Hawke adaptors/reducers are manufactured as standard in brass.

Adaptor Ordering Example

476/Male Thread Size/Female Thread Size.

e.g. 476/I/M25/M20.

Reducer Ordering Example

476/I/Male Thread Size/Female Thread Size.

e.g. 476/I/M25/3/4" NPT.

Application/Features

- Provides a means of connection between the equipment and cable glands with dissimilar thread sizes or types.

Technical Data

- Flameproof and Increased Safety EExde IIC.
 II 2 GD IP66.
- Certificate No. SIRA 06 ATEX 1240U.
- Suitable for use in Zone 1, Zone 2, Zone 21 and Zone 22.
- Suitable for use in Gas Groups IIA, IIB and IIC.
- Construction and test standards
EN 50014, EN 50018, EN 50019 and
EN 50281-1-1.
IEC 60079-0, IEC 60079-1 and IEC 60079-7.